

GYM SERIES

The diversity of indoor climbing walls and anchor systems, along with the constant falling and lowering of climbers, create some of the most challenging and abusive conditions for climbing ropes. This is why Sterling created its unique gym series. Sterling ropes are known for their durability and this has made them the leading choice of gym owners. Our gym ropes feature smooth handling, zero sheath slippage, and most important, the most durable construction to keep them in use in your gym longer.

Some gyms prefer non-dynamic gym ropes due to their top-rope setup. Sterling offers two low-elongation ropes suited for this purpose, including our new SafetyPro™ 10.5mm. All work well with various belay devices and are engineered to withstand frequent use and stay supple.




Julian Bautista at Youth Nationals.
Photo courtesy of USA Climbing.



Slim Gym 10.1mm

The perfect rope for testing your indoor lead skills whether it's on a rainy afternoon or in the heart of the urban jungle.


- Small diameter clips fast with little rope drag
- Durable Marathon sheath



Rock Gym 10.4mm

The "go to" rope for all of your gym's needs, at home on a lead route and psyched for top-roping.


- Popular diameter works well with most belay devices
- Durable Marathon sheath



Big Gym 10.7mm

The Granddaddy of gym ropes, beefy and tough. This rope is the standard for gyms and climbing programs the world over.

- Large diameter for top-rope set ups
- Durable Marathon sheath



Static Lines

Sterling offers two low elongation ropes: The 3/8" SuperStatic and 10.5mm SafetyPro. These ropes are offer low stretch, won't become stiff after extended top-rope use, and work well with all types of belay devices, including Gri-Gri's.

Warning: Low-Elongation ropes such as the 3/8" SuperStatic, and 10.5mm SafetyPro should never be used in lead climbing.

- Name	Slim Gym	Rock Gym	Big Gym	3/8" SS	10.5 SP
- Diameter	10.1mm	10.4mm	10.7mm	10mm	10.5mm
- Type	Single	Single	Single	Static	Static
- UIAA Falls	6	8	8	N/A	N/A
- Impact Force	8.6kN	8.5kN	8.6kN	N/A	N/A
- Static Elongation	8.4%	8.1%	9.0%	N/A	N/A
- Dynamic Elongation	35.5%	33.2%	36.1%	N/A	N/A
- Sheath Slippage	0mm	0mm	0mm	0mm	0mm
- Weight (gr/M)	63	67	70	62	70
- UIAA	Yes	Yes	Yes	N/A	N/A
- CE	Yes	Yes	Yes	Yes	Yes



26 Morin Street Biddeford, Maine
ph. 207.282.2550 f. 207-282-2655

www.sterlingrope.com